

T2365/T2365 HD



Tally

The T2365 series printers represent top of the line print speeds, rugged durability and unsurpassed performance under the most extreme conditions. These workhorse printers guarantee crisp, dark, clear and legible print thanks to the advanced engineering of the 24 pin print head. This head is built for long life and a heavy workload so even in the most challenging operating environment, you can be assured of the best in quality and performance.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

Highlights at a glance:

- Up to 9 part forms
- Full range of automatic features to minimize user intervention
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Interfaces: RS232 Serial; Coax/Twinax; Ethernet IPDS
- Straight through paper path for easy forms loading
- Compatible with a wide range of operating systems and legacy systems

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Fully automated operation, coupled with the 'straight through' paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Available Configuration:




- **T2365** Standard Product
- **T2365 2T** with additional rear tractor
- **T2365 HD** Heavy duty version for up to 9-parts
- **T2365 HD 2T** Heavy duty version with additional rear tractor

T2365/T2365 HD

Print Speed	900 cps (Fastest Draft); 640 cps (Draft), 180 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	605 pages per hour
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million strokes per pin
Standard Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Ethernet 10/1q00 BaseT
Optional Connectivity	RS-232 Serial, Ethernet with SCS or IPDS, Coax/Twinax with SCS or IPDS
Standard Emulation	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP, Genicom ANSI
Optional Emulation	PCL 3 (Rugged Writer), IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable LCP
Consumables	Ribbon: 20 million characters
Standard Paper Handling	Push tractor for continuous paper with straight paper path, tear off and park position
Optional Paper Handling	Additional push tractor (front), Automatic cutting device
Number of Copies	Push tractor front: 1 original + 5 copies or 1 original + 8 copies (HD version only) Push tractor rear: 1 original + 3 copies (2T version)
Paper Type	Continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 3" to 16.5"; Length: 3" to 22"
Physical Weight	19 kg
Physical Size	24.5" x 17" x 11" mm (W x D x H)
Acoustic	59 dB(A)
Power Voltage	120 V or 230 V (selectable)
Power Consumption	60 Watt Printing; 18 W Power Save
Temperature	+10° to +35° C; 20% to 80% humidity (not condensing)
Workload	48,000 pages per month
MTBF	12,500 hours
Warranty	90 days on-site warranty
Drivers	Windows 2000/XP/Vista/7/10 and Server 2003/2008; SAP
Note	For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase.

DASCOM Americas Corporation

34 Lakeview Ct.
Verona, VA
USA 24482
Tel: 877 434 1377
www.dascomamericas.com

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
FLATBED PRINTERS 
THERMAL PRINTERS 